


INT UNIT  
(J12)

D43/D44

Y3 Y0 Y7 Y6 Y5 Y4

downloaded by  
Amateur Radio Directory  
www.hamdirectory.info



PER AVERE I TONI CTCSS  
OCORRE SISTEMARE I DIODI  
PER LA VERSIONE U.S.A. #08 #03  
(A)

To have CTCSS  
tones it's necessary  
to place diodes as  
per USA version #08 and #03

• IC-275A/E

Area	D20	D21	D22	D23	D24
#06E	X	X	O	X	O
#08A	O	X	X	X	X
#10A	X	O	X	X	X
#12E	O	O	X	X	O

• IC-275H

Area	D20	D21	D22	D23	D24
#02H	X	X	O	X	O
#03H	O	X	X	X	X
#04H	X	O	X	X	X
#05H	O	O	X	X	O

O: MOUNTING X: NO MOUNTING

(B)

downloaded by  
Amateur Radio Directory  
www.hamdirectory.info

• IC-275A/E

Area	D43	D44
#06E	X	O
#08A	O	X
#10A	O	O
#12E	O	O

EUROPE  
• USA

• IC-275H

Area	D43	D44
#02H	X	O
#03H	O	X
#04H	O	O
#05H	O	O

EUROPE  
• USA

O: MOUNTING X: NO MOUNTING

O: INSERITO X: TAGLIATO


Thanks to MARCUCCI S.p.A. for informations provided

# • LOGIC UNIT

D20  
D21  
D22  
D23  
D24

downloaded by  
Amateur Radio Directory  
www.hamdirectory.info

Thanks to MARCUCCI S.p.A.  
for informations provided



downloaded by  
Amateur Radio Directory  
www.hamdirectory.info